ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. NO. 3067-0077 Expires May 31, 1996

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to vide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to rmine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages. SECTION A PROPERTY INFORMATION FOR INSURANCE COMPANY USE BUILDING OWNER'S NAME POLICY NUMBER GREG ROBERTSON (WEST MONTHS CHEIRAU) STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg, Number) OR P.O. ROUTE AND BOX NUMBER COMPANY NAIC NUMBER 13885 FRYELANDS DLVD OTHER DESCRIPTION (Lot and Block Numbers, etc.) LOT A U. 540G 26192017 CITY STATE maviore. ZIP CODE 98272 SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 1. COMMUNITY NUMBER 2. PANEL NUMBER 3. SUFFIX 4. DATE OF FIRM INDEX 5. FIRM ZONE 6. BASE FLOOD ELEVATION (in AO Zones, use depth) 430169 0001 飞 Dec 1,1983 A-5 30 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: Liliand letter NGVD (or other FIRM datum-see Section B, Item 7). SECTION C BUILDING ELEVATION INFORMATION 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level _____.). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 1 33.12 feet NGVD (or other FIRM datum-see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of ______ feet NGVD (or other FIRM datum-see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is _____ feet above ___ or below [] (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is _____ feet above __ or below __ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference 3. Indicate the elevation datum system used in determining the above reference level elevations: M NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Tes X No. (See Instructions on Page 4) 5. The reference level elevation is based on: 🛛 actual construction 🔲 construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which

SECTION D COMMUNITY INFORMATION

1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest ricor" as defined by the ordinance is: ______ feet NGVD (or other FIRM datum-see Section B, Item 7).

case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate

6. The elevation of the lowest grade immediately adjacent to the building is: 1 32.7 feet NGVD (or other FIRM datum-see

2. Date of the start of construction or substantial improvement

will be required once construction is complete.)

Section B. Item 7).


SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1—A30, AE, AH, A (with BFE),V1—V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

HAROLD F PETERSON	WA PE 201	504	
CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seal)		
PRESIDENT	PETERSON CONSULT	PETERSON CONSUME ENGRY INC	
ITLE	COMPANY NAME		_
JEV ZNO AKE S	KIRKLAND	<u> ১৯ </u>	
ADDRESS	CITY GIZUI97	(206) 827-5874	ZIP
SIGNATURE	DATE	PHONE	
COMMENTS:			
COMMENTS:			
			· · · · · · · · · · · · · · · · · · ·
	, , , , , , , , , , , , , , , , , , , ,		
			.,,-



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.